



HTL 3-in-1 Hydraulic Torque Wrench

HTL's innovative 3-in-1 Hydraulic Torque Wrench is part of a modular system which is made up of a single power head and three attachments; the Low Profile, Square Drive and Ultra-Low. The HTL 3-in-1 Hydraulic Torque Wrench is able to solve all of your bolting challenges quickly and safely, with one or more attachment options, making it suitable for any application.

Extremely durable, this premium tool is made from the highest quality materials and is amongst the most innovative torque tooling designed to date. This ensures that with the use of the HTL 3-in-1, the operator can not only utilise various attachments to suit any application, but also interchange these with many other well-known brands (specifically Hytorc, Rapid-Torc and Atlas Copco).

The tool, which is designed and manufactured in the UK, comes with a 12 month warranty and full CE and ATEX approval.

Operator Safety

To improve operator safety HTL have also designed an ergonomic, adjustable torque wrench handle which can be easily fitted to HTL's 3-in-1 Hydraulic Torque Wrench. This lightweight, durable accessory can prevent injuries such as trapped fingers by eliminating the need to hold the tool itself.

The HTL 3-in-1 Hydraulic Torque Wrench is also supplied with a link pin retainer as standard.

Features and Benefits

- ✓ Fully interchangeable with many other well-known brands (Hytorc, Rapid-Torc and Atlas Copco)
- ✓ Made in the UK
- ✓ Calibrated and accurate to +/- 3%
- ✓ Supplied with link pin retainer
- ✓ Torque range from 255 to 31,800 ft.lb, 346 to 43,100 Nm



Technical Information

Model		HTL-W2	HTL-W4	HTL-W8	HTL-W14	HTL-W30
Min Torque*	lb.ft	255	580	1143	2010	4770
	Nm	346	786	1549	2725	6466
Max Torque*	lb.ft	1710	3855	8151	13400	31800
	Nm	2318	5226	11049	18165	43108
Weight	Kg	0.9	1.9	3.2	5.1	11.3

*Min and Max Torque figures when used in conjunction with HTL-L Low Profile Attachment or equivalent.

HTL-W with Low Profile Attachment



HTL-W with Square Drive Attachment



HTL-W with Ultra-Low Attachment




Other Tools in the HTL 3-in-1 Hydraulic Torque Wrench Range...



HTL-W
Torque
Wrench



HTL-R
Ultra-Low
Attachment



HTL-L
Low Profile
Attachment



HTL-S
Square Drive
Attachment




HTL-OE
Open Ended
Spanner




HTL-RS
Ring Spanner




HTL-RP
Reaction Pad



HTL-SA
Square Drive
Adapter



HTL-HA
Hex
Adapter



HTL-HR
Hex
Reducer



HTL-IO
In/Out
Socket



HTL-EA
Extended Reaction Arm

PLEASE NOTE: Figures provided are for guidance only, please refer to individual tool charts. All data is given in good faith and without acceptance of responsibility on the part of HTL.

INDUSTRY LEADERS IN CONTROLLED BOLTING, FLANGE WORKING AND PORTABLE MACHINE SOLUTIONS



HTL Australasia Pty Ltd
466 Victoria Road
Malaga, WA 6090
Western Australia

Telephone: +61 (0) 8 9249 3980
Email: info@htl-australasia.com
Visit: www.htl-australasia.com

