



HTL Lubricants

Pro-Moly

The Smart Bolting Lubricant

Pro-Moly is a metal-free, lithium based, anti-seize lubricant that safeguards against corrosion whilst offering enhanced load carrying performance and wear protection.

Pro-Moly ideally suited for the assembly and fitting of a wide range of threaded connections such as bolted connections.

It offers a wide service temperature range and low, constant coefficient of friction ensuring that tightening torques can be calculated and applied accurately.

Pro-Moly also facilitates disassembly even after extended periods and after harsh and adverse conditions.

This smart lubricant is durable, reliable, water resistant and versatile making it the number one choice for bolting lubricant.



Pro-Copper

The High Performance Bolting Lubricant

Pro-Copper is a high temperature, anti-seize compound used to prevent seizure and galling during assembly even in the harshest pressure and temperature environments resulting in reduced assembly time. It also protects against rust, oxidation and chemical attack.

The unique combination of properties in Pro-Copper allows for the quick and easy assembly of threaded parts which also allows for accurate torque to be applied by reducing thread interference.

Pro-Copper is suitable as an anti-seize lubricant for a wide range of aggressive conditions including application to pipe fittings and valves in the chemical and petrochemical industry, gas refining and oil drilling equipment. It also reduces wear in areas of high friction resulting in the easy breakout of threads, gaskets and packings.

Due to its seizure protection qualities, maintenance work requiring routine or infrequent assembly and dismantling is made much easier and less costly.



Pro-Complex

Multipurpose grease

Pro-Complex is a lithium complex thickened blue coloured grease that has been developed as a multipurpose product recommended for use on industrial equipment where high temperatures are a challenge.

Pro-complex out performs conventional Lithium greases due to its exceptional mechanical stability to extend relubrication intervals and has excellent oxidation stability providing lasting lubrication in harsh high temperature environments.

This multipurpose grease offers first rate mechanical wear resistance ensuring durability and reliability.

It also has exceptional sealing properties which help protect bearings against corrosive atmospheres and it has a high degree of water tolerance when operating in wet conditions.



Pro-46 Hydraulic Oil

HTL's Pro - 46 Hydraulic Oil is a premium quality, high performance blue hydraulic oil designed to be used in HTL's range of Hydraulic Torque and Tension Pump Units. The oil incorporates a high-performance and improvement, carefully selected additive package which provides excellent anti-wear and extreme pressure properties as well as impressive thermal stability and corrosion protection.

This product performs across a wide temperature range and its exceptional anti-wear, lubricity and film strength characteristics guarantee performance in hydraulic and circulation systems performing even in severe conditions.



PLEASE NOTE: Figures provided are for guidance only, please refer to individual tool charts. All data is given in good faith and without acceptance of responsibility on the part of HTL.

INDUSTRY LEADERS IN CONTROLLED BOLTING, FLANGE WORKING AND PORTABLE MACHINE SOLUTIONS



HTL Australasia Pty Ltd
466 Victoria Road
Malaga, WA 6090
Western Australia

Telephone: +61 (0) 8 9249 3980

Email: info@htl-australasia.com

Visit: www.htl-australasia.com

